



Test Pac 1000

Pressure Test Unit



The Haskel Test Pac 1000 is a heavy duty test rig designed for shop floor and on site pressure testing.

The unit is self contained mounted on a mild steel base frame and powered by compressed air.

Suited for use in most industries including;

- Oil & Gas
- Petrochemical
- Power Generation
- Automotive
- Paper
- Food Industry
- Defence
- Aerospace
- Ship Building



Haskel Air Driven Liquid Pumps offer many advantages over conventional electrical driven power units.

- Ability to stall at any predetermined pressure and hold this fixed pressure without consuming power or generating heat.
- No heat, flame or risk of spark
- Infinitely variable cycling speed (flow rate)
- No limit or adverse effect to continuous stop/start applications
- Pump seals are self lubricated requiring no external air line lubricator

Reliable, easy to maintain, compact and robust





Model Selection Chart – Based on 6 barg air drive available***

PUMP MODEL	PRESSURE RANGE*** Barg	FLOW CAPACITY Litres/min	FLUID SERVICE	MODEL ORDERING CODE
D14STD-125	200 - 800	11.5	Water or Oil	J24035-D14STD-125
D14STD-315	500 - 2,000	4.5	Water or Oil	J24035-D14STD-315
D14SFD-125	200 - 800	11.5	Water or Oil	J24035-D14SFD-125
D14SFD-315	500 - 2,000	4.5	Water or Oil	J24035-D14SFD-315

Description

The Test Pac 1000 is a self-contained unit, which is supplied complete with the following

- Haskel air driven liquid pump
- Air controls comprising air filter, air pressure regulator, air gauge on/off speed control valve and air exhaust silencer
- Suction strainer
- Outlet 4” dial pressure gauge, glycerine filled with stainless steel case
- Pressure release valve
- Fluid outlet connection located at edge of frame
- All suitably piped mounted on a steel base frame (see photo)
- Unit is supplied finish painted Haskel Blue RAL 5017

Specification

Approx Dimensions 600mm x 1250mm x 750mm high

Approx Nett Weight 105 kgs

Air Drive Pressure Range 1.7 - 8.6 Bar

Connections -

- Air Inlet ¾” BSP (female).
- Hydraulic Inlet 1/2” NPT Female -
- Hydraulic Outlet 3/8” HP (female)

Haskel Energy Systems Ltd

North Hylton Road, Sunderland. SR5 3JD. England

Tel: 00 44 (0) 191 549 1212. Fax: 00 44 (0) 191 549 0911, E-mail sales@haskel.co.uk Web: www.haskel.com

Haskel International Inc.
Industrial Technologies Division
Tel : (1) 818 843-4000
Fax: (1) 818 844 291

Haskel France
Tel: (33) 03 20 04 66 00
Fax: (33) 03 20 33 31 95

Haskel Hochdrucksysteme
Tel: (49) 281 984 800
Fax: 281 984 8020

Haskel BV
Tel: (31) 79 36 18 472
Fax: (31) 79 36 00 560

Haskel Espana S.R.L.
Tel: (34) 943 474 566
Fax: (34) 943 451 186

Haskel Italiana S.R.L.
Tel: (39) 0331 987 596
Fax: (39) 0331 987 597

Haskel Australasia Pty. Ltd.
Tel: (61) 7 3277 9118
Fax: (61) 7 3277 6129

Haskel (Asia)
Tel: (65) 6455 7559
Fax: (65) 6455 2841